

## Whole window U Value: Wood / PVCU

Description Air Gap	6	8	10	12	14	16	18	20
4mm / 4mm Air	3.10	3.00	2.90	2.80	2.80	2.70	2.70	2.70
4mm / 4mm Air Gas	2.90	2.80	2.70	2.70	2.70	2.60	2.60	2.60
4mm / K / 4mm Air	2.70	2.50	2.40	2.20	2.10	<b>2.00</b>	<b>2.00</b>	<b>2.00</b>
4mm / K / 4mm Air Gas	2.40	2.30	2.10	<b>2.00</b>	<b>2.00</b>	<b>1.90</b>	<b>1.90</b>	<b>1.90</b>
<b>Warm Edge Spacer</b>								
4mm / S/C / 4mm Air	2.20	<b>2.00</b>	<b>1.80</b>	<b>1.60</b>	<b>1.50</b>	<b>1.40</b>	<b>1.40</b>	<b>1.40</b>
4mm / S/C / 4mm Air Gas	<b>1.90</b>	<b>1.70</b>	<b>1.60</b>	<b>1.40</b>	<b>1.40</b>	<b>1.30</b>	<b>1.30</b>	<b>1.30</b>

\*S/C = Soft Coat Low E

Values Highlighted in **RED** meet Document L requirement 2.0 W/m<sup>2</sup>K